

PASSAGEWAY STRUCTURE OF DISHWASHER

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to a dishwasher, and more particularly, to a dishwasher having a micro filter equipped with a self-purifying function placed at a passage of a dishwasher to filter wash liquid having a high concentration of soil particles.

Background of the Related Art

In general, dishwashers are machines for automatically washing dishes by injecting wash liquid which contains with a detergent. Dishwashers having two dish accommodating spaces, namely, two-stage dishwashers include, as shown in FIG.1, a case

10, upper and lower racks 20 which are installed on the case 10 to accommodate dishes, upper and lower injection arms 30 which are installed on a lower side of each rack 20, a circulating pump 40 for pressing and supplying wash liquid to the respective arms 30, a drain pump 50 for draining the wash liquid, and filtering means for filtering the wash liquid.

Here, the respective arms 30 are supported by an arm holder 34 which is connected to a feed pipe 32 so as to be horizontally rotated, and a plurality of injection nozzles 301 are installed

25 on an upper surface of the injection arms facing the respective racks 20.

1002260" T 2449560
In the circulating pump 40, a discharge slot is connected to the feed pipe 32 and the injection arms 30 to supply the wash liquid, and an inlet is connected to an underdrain container 60
30 which is comprised in the filtering means. The filtering means includes the underdrain container 60 which is provided on a lower part of a bottom surface at the inside of the case 10, and a first filter (rough mesh filter) 62 and a second filter (fine mesh filter) 64, which are installed within the underdrain container 60. The underdrain container 60 is opened toward a so-called washing space on an upper surface thereof, and connected to the circulating pump 40 on one side thereof and the drain pump 50 on a lower side thereof.

Here, the second filter 64 is configured in a shape of a
40 pipe connected with the drain pump 50 on a lower side thereof.

The first filter 62 is shaped like a filter net being provided within the second filter 64.

Operation of the aforesaid dishwashers of the conventional art is roughly divided into two stages, that is to say, a washing
45 stage and a draining stage. In the washing stage, the washing operation is carried out in a manner that the wash liquid formed with mixture of water and detergent is pressed and supplied to the upper and lower arms 30 by the circulating pump 40, and

injected to dishes d placed in the racks 20 by the injection
50 nozzles 301.

At this time, the wash liquid injected by the injection arms
30 is collected in the underdrain container 60 on the bottom, and
supplied to the injection arms 30 again by the circulating pump
40. This process is called a circulation operation. During the
55 course of the circulation, such soil as food residues separated
from the dishes d are filtered by the first and second filters 62
and 64, so as to prevent aggravated pollution of the wash liquid
(see FIG.2).

When the washing stage is finished with the lapse of a
predetermined period of time, the draining stage is then
initiated. During the draining stage, the wash liquid is drained
by the operation of the drain pump 50. As illustrated in FIG.2,
the soil with large particles is filtered by the first filter 62
and then remains within the first filter 62, thereby preventing a

65 drain outlet from being clogged. The soil with smaller particles
that passed through the first filter 62 are filtered at the
second filter 64, and then discharged together with the wash
liquid through the drain outlet 501 of the drain pump 50.

If the draining stage is finished and the operation of the
70 drain pump 50 is stopped, the wash liquid still remains in a
drain pipe 54 which connects the drain outlet 501 with a soil
ditch. Sometimes the residual wash liquid flows backward into an

inside of the dishwasher. In an attempt to prevent a backward
flow of the residual wash liquid, a check valve may be installed
75 on the drain outlet 501.

The check valve 70 prevents the backward flow of the
residual wash liquid in by allowing the wash liquid in the drain
pipe 54 to flow only from the drain outlet 501 to the soil ditch.
The washing and draining stages are performed once during what is
80 called one round of water filling. General, three or four rounds
of water filling are conducted during one dish washing cycle.
The washing and draining stages are accordingly performed,
thereby enhancing efficiency in dish washing.

The conventional art, however, has a disadvantage of
5 decreasing efficiency in washing, since a small particle soil is
adhered to the second filter 64 because of structural feature of
the second filter (fine mesh filter) 64, and not all of the
adhered soil is discharged during the draining stage, causing a
newly supplied wash liquid to be polluted.

90 The soil filtered by the first and second filters 62 and 64
should be removed after the washing is finally finished, however,
in the conventional art the small particle soil filtered by the
second filter 64 is difficult to remove although the larger
particle soil filtered by the first filter 62 can be more easily
95 removed.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a passage
100 structure of a dishwasher that substantially obviates one or more
problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a passage
structure of a dishwasher, which can filter wash liquid in a more
efficient manner by employing a predetermined passage on which a
105 micro filter is installed and enabling the micro filter to have a
self-purification capacity.

Additional advantages, objects, and features of the invention
will be set forth in part in the description which follows and in
part will become apparent to those having ordinary skill in the
110 art upon examination of the following or may be learned from
practice of the invention. The objectives and other advantages of
the invention may be realized and attained by the structure
particularly pointed out in the written description and claims
hereof as well as the appended drawings.

115 These and other objects are satisfied by a passage structure
of a dishwasher including, a circulating pump for pressing and
then supplying wash liquid, an injection arm for permitting the
wash liquid pressed and supplied from the circulating pump to be
injected by a predetermined passage structure, an underdrain
120 container for collecting the wash liquid injected from the

injection arm and supplying the collected wash liquid to the circulating pump, during a washing stage, a soil collecting chamber having a micro filter with a fine mesh for ramifying and finely filtering the wash liquid supplied from the circulating pump and returning the same to the underdrain container, during the washing stage, a drain pump for allowing the wash liquid to be drained through a drain passage which is extended from the underdrain container, and through a connecting passage which is extended from the soil collecting chamber and connected to the drain passage, during a draining stage.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the invention and together with the description serve to explain the principle of the invention. In the drawings: FIG.1 is a sectional view showing a construction of a general dishwasher;

FIG.2 is a sectional view illustrating a filtering operation of a

145 conventional filtering means applied to the general dishwasher;
FIG.3 is a plan view showing a construction of essential parts of
a dishwasher according to a preferred embodiment of the present
invention;
FIG.4a and FIG.4b are sectional views of a filtering operation
150 and a draining operation of a micro filter employed to the
dishwasher according to the preferred embodiment of the present
invention; and
FIG.5 is an enlarged plan view showing a construction of
essential parts of a dishwasher according to another preferred
155 embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred
embodiments of the present invention, examples of which are
160 illustrated in the accompanying drawings. Similar reference
numerals identify corresponding parts.

Referring to FIG.3, a filtering means employed in a
dishwasher according to a preferred embodiment of the present
invention includes a net filter 63 being installed in an
165 underdrain container 60, a soil collecting chamber 80 (see FIG.4)
which is provided on a bottom surface within the case 10 and
connected to a discharge slot 401 of a circulating pump 40 and to
an inlet 502 of a drain pump 50, a micro filter 82 placed on an

upper surface of the soil collecting chamber 80, and an auxiliary
170 injection nozzle 302 which is installed on a lower surface of an
injection arm 30 and injects wash liquid to the micro filter 82.
Here, the net filter 63 is a sort of rough mesh filter and filters
soil having larger particles, whereas the micro filter 82 is a
sort of fine mesh filter relative to a net filter 63 and filters
175 soil having smaller particles.

099447
180 1803260
The auxiliary nozzle 302 is placed with a predetermined
distance from a center of rotation of the injection arm 30, so as
to pass an upper side of the micro filter 82 when the injection
arm 30 is rotated, and also formed on a lower side of the
injection arm 30 so as to strike an upper surface of the micro
filter 82.

A check valve 72 is provided on a drain passage 60a that
connects the underdrain container 60 to the drain pump 50 to
prevent wash liquid from flowing backward into the underdrain
185 container 60. The check valve 72 is placed at a position close
to the underdrain container 60 based on a connecting passage with
the soil collecting chamber 80.

Operation of the dishwasher according to the preferred
embodiment will be explained on the basis of wash liquid
190 filtering operation.

Initially, the wash liquid filtering operation according to the
preferred embodiment is divided into a main filtering operation

through the net filter 63 and an auxiliary filtering operation through the micro filter 82. The main filtering operation is carried out in such a manner that all of the wash liquid discharged from the injection arm 30 passes through the net filter 63 during one circulation cycle, whereby the soil having larger particles is filtered.

Then, the auxiliary filtering operation is carried out in such a manner that a partial volume of the wash liquid discharged from the circulating pump 40 is flowed into the soil collecting chamber 80 through the discharge slot 401, and then upwardly ejected through the micro filter 82, whereby the fine soil which has not been filtered by the net filter 63 is filtered through the micro filter 82.

If the wash liquid is repeatedly circulated for a predetermined number of times, the auxiliary filtering operation has the same effect that the total volume of wash liquid is filtered through the micro filter 82. Accordingly the fine soil contained in the wash liquid is entirely filtered.

In the injection arm 30, the wash liquid is upwardly injected from a plurality of injection nozzles 301 which face upward to wash dishes and the wash liquid is downwardly injected from the auxiliary nozzles 302 which face downward. Since the downwardly injected wash liquid strikes an upper part of the micro filter 82 intermittently, soil particles adhered on a lower

surface of the micro filter 82 are removed, thereby a self-purification function is achieved.

Therefore, the soil collected in the soil collecting chamber 80 is maintained in a floated condition within the soil collecting chamber 80 by virtue of the aforesaid self-purification function preventing the soil from being adhered on the micro filter 82, which may partially clog the micro filter.

When the draining stage is conducted after the end of the washing stage, as shown in FIG.4b, the soil particles collected in the soil collecting chamber 80 is drawn together with the wash liquid into the drain passage 60a by the drain pump 50 via the connecting passage 80a before being discharged. As a result, the micro filter 82 does not need to be separately cleaned.

According to the preferred embodiment of the present invention, in the course of the first washing or the repeated circulation of wash liquid after the end of the draining stage,

the check valve 72 prevents the wash liquid remaining on the drain passage 60a and the soil collecting chamber 80 from flowing backward into the underdrain container 60. In particular, the reason why the check valve 72 is installed near the underdrain container 60 based on the connecting passage 80a on the drain passage 60a is that it prevents the soil collected in the soil collecting chamber 80 from being flowing backward into the underdrain container 60.

Meantime, in the event that the volume of residual wash liquid is heavy, the backward flow of the wash liquid into the underdrain container 60 is prevented with the aid of the check valve 72. However, the wash liquid may still flow backward
245 toward the soil collecting chamber 80, causing the wash liquid to be polluted.

In order to prevent the wash liquid from flowing backward, still another preferred embodiment of the present invention, as shown in FIG.5, further employs an auxiliary check valve 74
250 placed in the connecting passage 80a which connects the soil collecting chamber 80 with the drain passage 60a. Even if the volume of the residual wash liquid is large, the auxiliary check valve 74 can block the wash liquid from flowing backward into the soil collecting chamber 80.

Referring to FIG.4 or FIG.5, the drain pump 50 may be
255 integrally formed with the circulating pump 40, without being separated from each other. Even if a single motor is used and the combination drainage/circulating pump is coaxially formed, when the respective passages are connected to the pertinent
260 positions of the same pump, the operation of the system will not be effected regardless of whether the drain pump 50 is integrated with the circulating pump 40.

As stated above, the dishwasher according to the present invention has an advantage of preventing newly supplied wash

265 liquid from being polluted, since the soil particles filtered by
the micro filter in the washing stage are smoothly discharged in
the draining stage. And also since the micro filter is self-
purified, troublesome process of additionally removing the soil
particles after dish washing has been eliminated, thereby
270 improving efficiency in washing and convenience in use.

The forgoing embodiments are merely exemplary and are not to
be construed as limiting the present invention. The present
teachings can be readily applied to other types of apparatuses.
The description of the present invention is intended to be
275 illustrative, and not to limit the scope of the claims. Many
alternatives, modifications, and variations will be apparent to
those skilled in the art.

096441-092801
275
T03250-T449660